

43 Inch Outdoor Touchscreen Digital Kiosk

KEY FEATURES	PICTURE
A+ LCD IPS Panel FHD 1920x1080 Brightness ≥ 1500 nits 7*24 Hours working uninterrupted Projected capacitive touchscreen Energy-efficient components Vandal-resistant tempered glass Wi-Fi, 4G/5G & LAN connectivity Compatible with CMS platforms Optional: 1. Player alone / Network / Touchscreen 2. IP Rating: IP55 / IP65 3. OS: Windows / Android / Linux / None 4. Color Options: Grey, White, Black...	

Specification Table:

Digital Signage Size		43"
Model Number		ST- ITS-T43TA
PANELS	Panel Type	A+ LCD IPS Panel 43 inch
	Active Area	941.2x529.3 mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080 (FHD)
	Display Colors	16.7M
	Brightness	1500+ nits Sunlight-readable
	Contrast Ratio	1200:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤5ms
	S-System	PAL / NTSC / SECAM
	Life Expectancy	60000 Hours
FUNCTIONS	OS	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G, 5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Log Management	Support terminal log and playlist log
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special Outdoor Powder
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system Air-conditioner system
	Tempered Glass	6-8 mm (AG, AR or Laminated only in requirement)
	IP Rating	Air-cooling≤IP55 Air-conditioner≥IP65
	Speakers	2*10W Stereo
	I/O Connectivity	HDMI, RJ-45, USB, SD Card
	Dimensions	1450x1170x857 MM, Customizable
	N.W / G.W	56 KG / 79 KG (for Reference)
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-30°C to 55°C
	Storage Temp	-35°C to 60°C
	Working Humidity	10% to 90%
	Storage Humidity	10% to 90%
POWER	Voltage	AC 100V - 240V
	Watts	300W – 700W (by heat-control system)
	Standby	≤ 3W
	Power Mode	Manual Automatic Timer-setting On or Off

DIMENSION REFERENCE:

(Dimensions might be adaptable by different enclosures and heat-control systems)

REMARK

Pictures & Parameters here are for reference only. All referred to physical Products.
Final explanations belong to SUNTUNE SignageHub.

43 Inch Outdoor Touchscreen Digital Kiosk

