

49 Inch Non-Touch Outdoor Signage

KEY FEATURES

A+ LCD IPS panel
FHD 1920x1080
Brightness: **2000+** Nits
7*24 Hours working uninterrupted

Energy-saving WLED backlight
Sun-readable, Auto-Light sensor
Weather-proof with **IP65**-rated enclosure
Slim profile for flexible installation options
Vandal-resistant and low-maintenance design

Optional:

1. Player alone / Network / Touchscreen
2. Fan-cooling≤IP55 / Air-conditioning≥IP65
3. OS: Windows / Android / Linux / None
4. Color Options: Grey, White, Black...

PICTURE



Specification Table:

Digital Signage Size		49"
Model Number		ST- NTK-F49RA
PANEL	Panel Type	A+ LCD IPS Panel 49 inch
	Active Area	1073.8x604 mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080
	Display Colors	16.7M
	Brightness	2000+ nits Sunlight-readable
	Contrast Ratio	1200:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤5ms
	S-System	PAL / NTSC / SECAM
	Life Expectance	60000 Hours
FUNCTIONS	Operation System	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G, 5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Log Management	Support terminal log and playlist log
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special Outdoor Powder
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system Air-conditioner system
	Tempered Glass	6-8 mm (AG, AR or Laminated only in requirement)
	IP Rating	Air-cooling≤IP55 Air-conditioner≥IP65
	Speakers	2*10W Stereo
	I/O Connectivity	DP, HDMI, RJ-45, USB, SD Card
	Dimensions	1980x780x255 MM, Customizable
	N.W / G.W	140KG / 176KG (for Reference)
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-30°C to 55°C
	Storage Temp	-35°C to 60°C
	Working Humidity	5% to 95%
	Storage Humidity	5% to 95%
POWER	Voltage	AC 100V - 240V 50/60Hz
	Watts	600W – 1kW (Due to heat-control system)
	Standby	≤ 3W
	Power Mode	Manual Automatic Timer-setting On or Off

DIMENSIONS (Reference):



(Dimensions might be adaptable by different enclosures and heat-control systems)

DECLARE:

Pictures and Parameters here are for reference alone. All standardized to physical products.
The final explanations belong to SUNTUNE SignageHub.

Website: www.suntunesignage.com Hotline: (+86) 188-2025-4103 Email : info@suntunesignage.com

Address : Bldg F10, Gangshen Center, Xinniu Rd, Minzhi Str, Longhua Dist., Shenzhen 518131, Guangdong, China.

49 Inch Non-Touch Outdoor Signage

